

Polys P-1a 850W



	2
1.	3
2.	3
3.	4
4.	4
4.1	Polys P-1a 850W SOLO	4
4.2	SP-1a 850W MINI	4
4.3	SP-1a 850W HOBBY	4
5.	5
5.1	5
5.2	5
5.3	5
5.4	5
5.5	5
5.6	5
6.	6
6.1	6
6.2	6
6.3	6
7.	7
8.	7
9.	8

1.

DYTRON –

2.

Polys P-1a 850W



« » 2



180–280°C

(1)
(2)
(3)

5-7°

320°

5.

5.1



DIN.

16-125

Polys P-1a 850W
6-) 6

16-75



5.2

-4 -1.



5.3

-4 -1.

5.4



5.5

-4 -1.

5.6

40



6.



6.1

6.2



- 1...150–175°C
- 2...175–195°C
- 3...195–215°C
- 4...215–235°C
- 5...235–255°C
- 6...255–280°C

1 2 3

(2)

(3)

180–280°C

(1)

6

PN10,

260°C.

– 260°C.

(3)

5-10

(1),

(3)

6.3

(.) .

()

9.

- 1.
- 2.
- 3.
- 3.1.
- 3.2.
- 3.3.
- 3.4.

24

DYTRON
DYTRON.

6

- 4.
- 5.
- 5.1.
- 5.2.
- 5.3.
- 5.4.
- 5.5.
- 5.6.
- 5.7.
- 6.
- 7.

.3.1.,

.1.